

Mercedes-Benz Actros 4048 S (6X4)



*Body karoseri tidak termasuk dalam penjualan.

Mercedes-Benz Actros 4048 S (6X4)

Roda & ban / Wheel & tyre	Konfigurasi roda penggerak / Drive configuration Ukuran roda / Wheel size Ukuran & tipe ban depan / Front tyre size & type Ukuran & tipe ban belakang / Rear tyre size & type	6X4 8.50 x 24 325 / 95 R 24, radial, tube-type, off-road pattern 325 / 95 R 24, radial, tube-type, off-road pattern
Mesin / Engine	Tipe / Type Emisi / Emission Isi silinder / Cylinder volume Tenaga maksimum / Max. power Torsi maksimum / Max. torque	OM471LA, 6 cylinder Euro 5 12.809 476 / 1,600 2,300 / 1,100
Transmisi / Transmision	Tipe / Type Jumlah gigi / Total gears Gear ratio/ Perbandingan gigi	G 280-16 PowerShift 3, Automated Manual (AMT) 16 Speed Forward + 4 Speed Reverse 11.722-0.687
Aki / Battery		2 X 12V, 170 Ah
Kopling / Clutch	Tipe / Type	Dry, Double Plate, Automatic Controlled (No Pedal)
Kapasitas tangki BBM / Fuel tank capacity	Diameter (mm) Tangki BBM utama / Main fuel tank (L) Tangki BBM tambahan / Additional fuel tank (L)	400 390 -
Kapasitas tangki AdBlue / AdBlue tank capacity	(L)	60
Sumbu depan / Front axle	Kapasitas beban maksimum / Max. capacity (kg)	8,000
Sumbu belakang / Rear axle	Kapasitas beban maksimum / Max. capacity (kg) Perbandingan gigi terakhir/ Final gear ratio Differential Lock	32,000 (16,000 + 16,000) 6.000 Inter-Wheel & Inter-Axle Parabolic, with Shock Absorber & Stabilizer
Suspensi / Suspension	Depan / Front Belakang / Rear	Parabolic, with Shock Absorber & Stabilizer Parabolic, with Shock Absorber & Stabilizer
Rem / Brake	Rem utama / Main brake Rem tambahan / Additional brake	Drum, Full Air, Dual Circuit, S-Cam, Electronic Braking System with ABS & ASR Engine Brake, Exhaust Brake, Trailer Brake
Dimensi / Dimension	Jarak sumbu roda / Wheelbase (WB) (mm) Jarak antar sumbu roda belakang / Distance between rear axles (TS) (mm) Panjang total / Total length (TL) (mm) Lebar total / Total width (TW) (mm) Tinggi total / Total height (TH) (mm) Radius putar / Turning circle radius (mm) JBB / GVW (kg) JBKB / GCW (kg)	3,850 1,450 7,713 2,500 3,823 8,824 40,000 63,600
Power Take-Off (PTO)	Tipe / Type Perbandingan & putaran / Ratio & rotation Pengendalian PTO / PTO control	Transmission PTO - Spline 0.95, Counter-Clockwise Electro-Pneumatic
Fifth wheel coupling		Just JSK38C, 3.5 inch Kingpin

Foto, konfigurasi, spesifikasi dan warna produk pada brosur ini dapat berbeda dari produk-produk yang masuk ke Indonesia.
Perubahan pada produk dapat terjadi sejak brosur ini dibuat (03.23).
Untuk konfirmasi lebih lanjut, silahkan hubungi Authorized Mercedes-Benz Commercial Vehicles Dealers Anda.

