

Mercedes-Benz Arocs 4042 K (6X4)



Mercedes-Benz Arocs 4042 K (6X4)

Roda & ban / Wheel & tyre	Konfigurasi roda penggerak / Drive configuration		6X4
	Ukuran roda / Wheel size		8.50 x 24
	Ukuran & tipe ban depan / Front tyre size & type		325 / 95 R 24, radial, tube-type, off-road pattern
	Ukuran & tipe ban belakang / Rear tyre size & type		325 / 95 R 24, radial, tube-type, off-road pattern
Mesin / Engine	Tipe / Type		OM471LA, 6 cylinder
	Emisi / Emission		Euro 5
	Isi silinder / Cylinder volume	(L)	12.809
	Tenaga maksimum / Max. power	(PS/rpm)	421 / 1,600
	Torsi maksimum / Max. torque	(Nm/rpm)	2,100 / 1,100
Transmisi / Transmision	Tipe / Type		G 280-16 PowerShift 3, Automated Manual (AMT)
	Jumlah gigi / Total gears		16 Speed Forward + 4 Speed Reverse
	Gear ratio/ Perbandingan gigi		11.722-0.687
Aki / Battery			2 X 12V, 170 Ah
Kopling / Clutch	Tipe / Type		Dry, Double Plate, Automatic Controlled (No Pedal)
Kapasitas tangki BBM / Fuel tank capacity	Diameter	(mm)	400
	Tangki BBM utama / Main fuel tank	(L)	390
	Tangki BBM tambahan / Additional fuel tank	(L)	-
Kapasitas tangki AdBlue / AdBlue tank capacity		(L)	60
Sumbu depan / Front axle	Kapasitas beban maksimum / Max. capacity	(kg)	8,000
Sumbu belakang / Rear axle	Kapasitas beban maksimum / Max. capacity	(kg)	32,000 (16,000 + 16,000)
Suspensi / Suspension	Perbandingan gigi terakhir/ Final gear ratio		6.000
	Differential Lock		Inter-Wheel & Inter-Axle
Rem / Brake	Depan / Front		Parabolic, with Shock Absorber & Stabilizer
	Belakang / Rear		Parabolic, with Shock Absorber & Stabilizer
Rem / Brake	Rem utama / Main brake		Drum, Full Air, Dual Circuit, S-Cam, Electronic Braking System with ABS & ASR
	Rem tambahan / Additional brake		Engine Brake & Exhaust Brake
Dimensi / Dimension	Jarak sumbu roda / Wheelbase (WB)	(mm)	4,150
	Jarak antar sumbu roda belakang / Distance between rear axles (TS)	(mm)	1,450
	Panjang total / Total length (TL)	(mm)	8,225
	Lebar total / Total width (TW)	(mm)	2,500
	Tinggi total / Total height (TH)	(mm)	3,834
	Radius putar / Turning circle radius	(mm)	9,402
	JBB / GVW	(kg)	40,000
	JBKB / GCW	(kg)	-
Power Take-Off (PTO)	Tipe / Type		Transmission PTO - Spline
	Perbandingan & putaran / Ratio & rotation		0.95, Counter-Clockwise
	Pengendalian PTO / PTO control		Electro-Pneumatic

Foto, konfigurasi, spesifikasi dan warna produk pada brosur ini dapat berbeda dari produk-produk yang masuk ke Indonesia. Perubahan pada produk dapat terjadi sejak brosur ini dibuat (03.23). Untuk konfirmasi lebih lanjut, silahkan hubungi Authorized Mercedes-Benz Commercial Vehicles Dealers Anda.

