

# Mercedes-Benz

## Arocs 4045 AK (6X6)



\*Body karoseri tidak termasuk dalam penjualan.

### Mercedes-Benz Arocs 4045 AK (6X6)

Roda & ban / Wheel & tyre	Konfigurasi roda penggerak / Drive configuration		6X6	
	Ukuran roda / Wheel size		8.50 x 24	
	Ukuran & tipe ban depan / Front tyre size & type		325 / 95 R 24, radial, tube-type, off-road pattern	
	Ukuran & tipe ban belakang / Rear tyre size & type		325 / 95 R 24, radial, tube-type, off-road pattern	
Mesin / Engine	Tipe / Type		OM471LA, 6 cylinder	
	Emisi / Emission		Euro 5	
	Isi silinder / Cylinder volume	(L)	12.809	
	Tenaga maksimum / Max. power	(PS/rpm)	449 / 1,600	
	Torsi maksimum / Max. torque	(Nm/rpm)	2,200 / 1,100	
Transmisi / Transmision	Tipe / Type		G 280-16 PowerShift 3, Automated Manual (AMT)	
	Jumlah gigi / Total gears		16 Speed Forward + 4 Speed Reverse	
	Gear ratio/ Perbandingan gigi		11.722-0.687	
Aki / Battery			2 X 12V, 170 Ah	
Kopling / Clutch	Tipe / Type		Dry, Double Plate, Automatic Controlled (No Pedal)	
Kapasitas tangki BBM / Fuel tank capacity	Diameter	(mm)	400	
	Tangki BBM utama / Main fuel tank	(L)	390	
	Tangki BBM tambahan / Additional fuel tank	(L)	-	
Kapasitas tangki AdBlue / AdBlue tank capacity		(L)	60	
Sumbu depan / Front axle	Kapasitas beban maksimum / Max. capacity	(kg)	8,000	
Sumbu belakang / Rear axle	Kapasitas beban maksimum / Max. capacity	(kg)	32,000 (16,000 + 16,000)	
Suspensi / Suspension	Perbandingan gigi terakhir / Final gear ratio		6.000	
	Differential Lock		Inter-Wheel & Inter-Axle	
	Depan / Front		Parabolic, with Shock Absorber & Stabilizer	
Rem / Brake	Belakang / Rear		Parabolic, with Shock Absorber & Stabilizer	
	Rem utama / Main brake		Drum, Full Air, Dual Circuit, S-Cam, Electronic Braking System with ABS	
Rem / Brake	Rem tambahan / Additional brake		Engine Brake & Exhaust Brake	
	Dimensi / Dimension	Jarak sumbu roda / Wheelbase (WB)	(mm)	4,450
Jarak antar sumbu roda belakang / Distance between rear axles (TS)		(mm)	1,450	
Panjang total / Total length (TL)		(mm)	8,525	
Lebar total / Total width (TW)		(mm)	2,500	
Tinggi total / Total height (TH)		(mm)	3,939	
Radius putar / Turning circle radius		(mm)	10,006	
JBB / GVW		(kg)	40,000	
JBKB / GCW		(kg)	-	
Power Take-Off (PTO)		Tipe / Type		Engine PTO - Flange Transmission PTO - Spline
		Perbandingan & putaran / Ratio & rotation		Engine PTO: 1.22, Counter-Clockwise Transmission PTO: 0.95, Counter-clockwise
	Pengendalian PTO / PTO control		Engine PTO: Non-Switchable Transmission PTO: Electro-Pneumatic	

Foto, konfigurasi, spesifikasi dan warna produk pada brosur ini dapat berbeda dari produk-produk yang masuk ke Indonesia. Perubahan pada produk dapat terjadi sejak brosur ini dibuat (03.23). Untuk konfirmasi lebih lanjut, silahkan hubungi Authorized Mercedes-Benz Commercial Vehicles Dealers Anda.

